

## **Product Description**

The Multilink FWM-9X-D is a high density wall mount fiber distribution unit designed to support patching and splicing in one unit. The unit has 9 adapter panel positions allowing for a wide variety of fiber termination connector types and is equipped with a set of double lockable doors that are keyed differently to maintain separation and security for the Network and Distribution sides of the termination panels. The FWM-9X-D is a member of a larger family of Fiber Distribution Units.

## **General Specifications**

Dimensions: Weight:	17″ H x 21.2″ W x 5″ D 23 lbs.
Splice Trays:	(3) 1120-SSTP, 2000-SSTA, or 2020-SSTP (see below for individual tray capacities)
Material:	Steel
Coating:	Electrostatic polyester powder coat
Finish:	Black textured

## Ordering Information

Stock ID	<b>Description</b>
10-5283	FWM-9X-D (Black)
10-5281	FWM-9X-D (Off White)
70902K	1120-SSTP (12 Single Fusion Splice Tray)
70506K	2000-SSTA (24 Single Fusion Splice Tray)
70709K	2020-SSTP (24 Single Fusion Splice Tray)

NOTE: For details on available splice trays please refer to the Multilink Catalog

North America	Europe, Middle East & Africa	Latin & South America
Tel: +1 440 366 6966 Fax: +1 440 366 6802	Tel: +1 440 366 6966 Fax: +1 440 366 6802	Tel: +1 440 366 6966 Fax: +1 440 366 6802
Email: engsupport@gomultilink.com	Email: engsupport@gomultilink.com	Email: lasupport@gomultilink.com