Copyright 2015 Multilink Inc. • All rights reserved • Specifications subject to change without notice • Rev. July 31, 2015









Product Description

The 336S Traffic Control Cabinet has been evaluated to FDOT specification 785 (FA 5-16-13) and placed on the Florida Department of Transportation's Approved Product List (APL).

Features

Swing open door equipped with piano hinges (3 places each door)

Hooks to place poly bag (document holder)

Stiffener brackets for door support (both doors)

3-point lock mechanism with Corbin #2 lock and gasket for weather tight seal

Bottom through drains any accumulated water / moisture to the outside

Air filter placed behind the intake vent plate, secured in place by a spring loaded clamp and directs incoming air downward.

Door stop holds the door open at 90° and 120° positions

Double flange surrounding door frames prevent water ingress

Sun shield (on both cabinet and doors)

Cover plate

Transfer switch enclosure (does not protrude inside)

Copyright 2015 Multilink Inc. • All rights reserved • Specifications subject to change without notice • Rev. July 31, 2015



Features Cont.

Green LED indicator light (mounted on the top)

Removable rack assembly - 19" EIA rack rails, zinc plated, holes tapped for 10-32 screws

Comes with 1RU sliding shelf w/ active work area of 15.25" x 11"

Equipped with electrical panel and ground bar along with cabined ground

Crowned top and sun shield to prevent standing water

Generator cord entrance is covered w/ metal plate when not in use

When generator cord is hood up, gasket attached at bottom seals the extra opening

Transfer switch comes w/ ability to change between utility power and generator power

Transfer switch has a 30AMP twist lock receptacle w/ recessed male contact for generator hook up

General Specifications

| Parameter | Specification |
|-------------|---|
| Dimensions: | 27.13"W x 52.75"H x 25.96"D |
| FDOT: | Meets specification 785 (FA 5-16-13) On the Florida Department of Transportation's Approved Product List Certification number 785-004-006 |
| Hardware: | All stainless steel External hardware is tamper proof Constructed of .125" thick 5052-H32 aluminum |
| Rating: | NEMA 3R standards |
| Fans: | Dual 4"-100 CFM fans w/ adjustable thermostat (32°F - 140°F) |
| Lighting: | Two 8 watt fluorescent bulbs controlled by door switches |
| Mounting: | Pole & Ground mountable |

Contact Us |

| North America | Europe, Middle East & Africa | Latin & South America | 1 |
|-----------------------------------|-----------------------------------|----------------------------------|---|
| Tel: +1 440 366 6966 | Tel: +1 440 366 6966 | Tel: +1 954 499 9203 | |
| Fax: +1 440 366 6802 | Fax: +1 440 366 6802 | Mobile: +1 305 684 2388 | |
| Email: engsupport@gomultilink.com | Email: engsupport@gomultilink.com | Email: hquinones@gomultilink.com | Ī |




Copyright 2015 Multilink Inc. • All rights reserved • Specifications subject to change without notice • Rev. July 31, 2015





Ordering


| Traffic Control Cabinet | | |
|-------------------------|-----------------------------|--|
| Stock ID | Description | |
| 030-238-50 | ITS Field Cabinet Type 336S | |

Dimensional Drawings









Contact Us |

| | North America | Europe, Middle East & Africa | Latin & South America | 1 |
|---|-----------------------------------|-----------------------------------|----------------------------------|---|
| | Tel: +1 440 366 6966 | Tel: +1 440 366 6966 | Tel: +1 954 499 9203 | |
| | Fax: +1 440 366 6802 | Fax: +1 440 366 6802 | Mobile: +1 305 684 2388 | |
| 1 | Email: engsupport@gomultilink.com | Email: engsupport@gomultilink.com | Email: hquinones@gomultilink.com | Γ |



Multilink Inc. 580 Ternes Ln Elyria, OH 44035 Tel: (440) 366-6966

Fax: (440) 366-6802









twitter.com/GoMultilink

youtube.com/GoMultilink

Email: hquinones@gomultilink.com

- i i i i

 North America
 Europe, Middle East & Africa
 Latin & South America

 Tel: +1 440 366 6966
 Tel: +1 440 366 6966
 Tel: +1 954 499 9203

 Fax: +1 440 366 6802
 Fax: +1 440 366 6802
 Mobile: +1 305 684 2388

Email: engsupport@gomultilink.com

Email: engsupport@gomultilink.com

Contact Us