



Slim Tap

Product Description

Multilink's Slim Tap was designed for low fiber count terminations for use in control panel and node cabinet installations. The small foot-print is ideal for situations where the rack in the cabinet is fully populated, and the tap can be mounted to the side wall. Quick installations and reduced construction costs are achieved with single ended terminations. The adapter panel design adds modularity and flexibility for the fiber jumpers. The removable feature also allow for repairs to a damaged connector in the field.

Specifications

Parameter	Specification
Dimensions:	2"W x 15"H x 2"D
Color:	Black
Material:	Aluminum
Finish:	Polyester Powder Coat
Mounting:	Pedestal Cabinet
Application:	Above Grade

Ordering Guide

SLTP					
	1	2	3	4	5

1	Fiber Count
06	6
12	12
24	24 (LC Only)

2	Adapter Type
SCU	SC/UPC
SCA	SC/APC*
LCU	LC/UPC
LCA	LC/APC*
ST	ST SM

*SM ONLY

3	Cable Type
OSP	Outside Plant
OSPA	Outside Plant Armored
FD	Flat Drop (12count Only)

4	Fiber Type
SM	Single Mode
OM1	OM1

5	Cable Length
XXXX	Custom (ft)

*ex: 100 ft = 0100



Multilink Inc.
580 Ternes Ln
Elyria, OH 44035
Tel: (440) 366-6966
Fax: (440) 366-6802



facebook.com/GoMultilink



twitter.com/GoMultilink



youtube.com/GoMultilink

© Multilink Inc. 2018 • All Rights Reserved