

8A24 HEI

SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	91 Ah
Capacity at C/20	79 Ah
Capacity at C/5	69.2 Ah
Weight	52 lbs. (24 kg)
Plate Alloy	Lead Calcium
Post Seal	Epoxy-Sealed
Container/Cover	Polypropylene

Caltrans BBS temperature range of -25°C to 74°C will be supported.

Temperature and battery age effect runtime.

Optimal Operating Temperature Range
-40°F (-40°C) - 140°F (60°C)

Charge Voltage @ 77°F (25°C)

Charge / Absorption / Equalize	2.30 - 2.43 VPC
Float / Standby	2.23 - 2.26 VPC

Vent Self-sealing

Terminal C (Insert w/ 1/4" - 20 round hole)



Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A. by East Penn Manufacturing Co., Inc.

Valve-Regulated, Absorbed Glass Mat Technology




DIMENSIONS

Inches (mm)

Length	10.90 (277 mm) including handle
Width	6.56 (167 mm)
Height	8.27 (210 mm)

AGM Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

For more information on this product and our full-range of solutions, contact Multilink at **440-306-7646**

