

FDH



Multilink’s Fiber Distribution Hubs are setting the standard for cross-connect configurations, configurable splitting, plug and play technologies and many other fiber architects. Our line of FDH cabinets can be ground mounted, pole mounted, and wall mounted. Customized cabinets are available and are designed in house by our highly talented engineering department. All FDH cabinets are designed to meet Telcordia and NEMA specifications.

FEATURES & BENEFITS

- Multilink’s 19” Rack-mountable Fiber Distribution Hub allows any 19” rack-mountable equipment to be mounted inside the cabinet.
- Custom 19” Plates allow the user to come up with a design that fits their network needs and mount them in standard rack rail footprints
- The SpliceHub™ has a dual door design that allows easy accessibility to both feeder and distribution partitions
- The SpliceHub™ can utilize our CT-X Cassettes which offer a plug and play design that supports any kind of input/output connectors

19” RACK RAIL CABINET

WWW.GOMULTILINK.COM/CATEGORIES/19-RACK-RAIL-CABINET



GENERAL INFORMATION

| | |
|-------------------------------|---------------------------|
| Dimension | 30.0”W x 36.0”H x 22.24”D |
| Rack Units | 15RU |
| Cable Entry/Exit Ports | 6 |
| Mounting | Ground, Pole, Wall |
| Standards | NEMA 4 Compliant |

SPLICE HUB™

WWW.GOMULTILINK.COM/CATEGORIES/SPLICE-HUB



GENERAL INFORMATION

| | |
|--------------------------|--------------------------------|
| Dimension | 16”W x 23”H x 20”D |
| Splitter Capacity | 9 |
| CT-X Capacity | 12 |
| Mounting | Ground, Pole, Vault |
| Connector Type | SC/UPC, SC/APC, LC/UPC, LC/APC |

SPLICE HUB™

WWW.GOMULTILINK.COM/CATEGORIES/SPLICE-HUB



GENERAL INFORMATION

| | |
|--------------------------|--------------------------------|
| Dimension | 12"W x 40"H x 22"D |
| Splitter Capacity | 9 (1x32) |
| CT-X Capacity | 24 |
| Mounting | Ground, Pole, Vault |
| Connector Type | SC/UPC, SC/APC, LC/UPC, LC/APC |